

**DOUBLE ENDED THREADED K. WIRE**

CAT. NO.	PRODUCT DESCRIPTION	MAT.
242.135	DOUBLE ENDED THREADED K. WIRE Ø 1.0 MML 150MM	SS
242.140	DOUBLE ENDED THREADED K. WIRE Ø 1.2 MML 150MM	SS
242.141	DOUBLE ENDED THREADED K. WIRE Ø 1.2 MML 200MM	SS
242.142	DOUBLE ENDED THREADED K. WIRE Ø 1.2 MML 250MM	SS
242.143	DOUBLE ENDED THREADED K. WIRE Ø 1.2 MML 300MM	SS
242.145	DOUBLE ENDED THREADED K. WIRE Ø 1.4 MML 250MM	SS
242.146	DOUBLE ENDED THREADED K. WIRE Ø 1.4 MML 150MM	SS
242.147	DOUBLE ENDED THREADED K. WIRE Ø 1.4 MML 200MM	SS
242.148	DOUBLE ENDED THREADED K. WIRE Ø 1.2 MML 250MM	SS
242.149	DOUBLE ENDED THREADED K. WIRE Ø 1.4 MML 300MM	SS
242.150	DOUBLE ENDED THREADED K. WIRE Ø 1.5 MML 150MM	SS
242.152	DOUBLE ENDED THREADED K. WIRE Ø 1.5 MML 200MM	SS
242.153	DOUBLE ENDED THREADED K. WIRE Ø 1.5 MML 250MM	SS
242.154	DOUBLE ENDED THREADED K. WIRE Ø 1.5 MML 300MM	SS
242.157	DOUBLE ENDED THREADED K. WIRE Ø 1.6 MML 150MM	SS
242.158	DOUBLEENDED- THREADED K. WIRE Ø 1.8 MML 300MM	SS
242.159	DOUBLE ENDED THREADED K. WIRE Ø 1.6 MML 250MM	SS
242.162	DOUBLE ENDED THREADED K. WIRE Ø 1.6 MML 300MM	SS
242.163	DOUBLE ENDED THREADED K. WIRE Ø 1.8 MML 150MM	SS
242.164	DOUBLE ENDED THREADED K. WIRE Ø 1.8 MML 200MM	SS
242.165	DOUBLE ENDED THREADED K. WIRE Ø 1.8 MML 250MM	SS

242.166	DOUBLE ENDED THREADED K. WIRE Ø 1.8 MM L 300MM	SS
242.202	DOUBLE ENDED THREADED K. WIRE Ø 2.0 MM L 150MM	SS
242.204	DOUBLE ENDED THREADED K. WIRE Ø 2 MM- L 200MM	SS
242.206	DOUBLE ENDED THREADED K. WIRE Ø 2 MM L 250MM	SS
242.207	DOUBLE ENDED THREADED K. WIRE Ø 2 MM L 300MM	SS
242.252	DOUBLE ENDED THREADED K. WIRE Ø 2.5 MM L 150MM	SS
242.254	DOUBLE ENDED THREADED K. WIRE Ø 2.5MM - L 200MM	SS
242.256	DOUBLE ENDED THREADED K. WIRE Ø 2.5 MM L 250MM	SS
242.258	DOUBLE ENDED THREADED K. WIRE Ø 2.5 MM L 300MM	SS
242.300	DOUBLE ENDED THREADED K. WIRE Ø 3 MM L 300MM	SS
242.302	DOUBLE ENDED THREADED K. WIRE Ø 3 MM L 150MM	SS
242.303	DOUBLE ENDED THREADED K. WIRE Ø 3 MM L 300MM	SS
242.304	DOUBLE ENDED THREADED K. WIRE Ø 3 MM L 200MM	SS
242.306	DOUBLE ENDED THREADED K. WIRE Ø 3 MM L 250MM	SS
242.345	DOUBLE ENDED THREADED K. WIRE Ø 3.5 MM L 150MM	SS
242.353	DOUBLE ENDED THREADED K. WIRE Ø 3.5 MM L 300MM	SS

## Specification

- All DOUBLE ENDED - THREADED K. WIRES are available in SS.

## Indication for use

- The Double Ended Threaded K-Wire is used for skeletal fixation in fractures, osteotomies, and other orthopaedic procedures. It provides temporary stabilization of bone fragments and is commonly used for fixation in small bone fractures, joint stabilization, and alignment during surgery. The threaded ends ensure secure anchorage and prevent migration of the wire during healing.

