



CAT.NO.	METAL	Kirschner's Wire (K. Wire)
241.057	SS	K. Wire Ø 0.6 mm- L 70mm
241.063	SS	K. Wire Ø 0.6 mm- L 150mm
241.065	SS	K. Wire Ø 0.6 mm- L 200mm
241.067	SS	K. Wire Ø 0.6 mm- L 250mm
241.079	SS	K. Wire Ø 0.8 mm- L 070 mm
241.085	SS	K. Wire Ø 0.8 mm- L 150mm
241.090	SS	K. Wire Ø 0.8 mm- L 300mm
241.098	SS	K. Wire Ø 1.0 mm- L 70mm
241.100	SS	K. Wire Ø 1.0 mm- L 100mm
241.102	SS	K. Wire Ø 1.0 mm- L 125mm
241.103	SS	K. Wire Ø 1.0 mm- L 150mm
241.105	SS	K. Wire Ø 1.0 mm- L 200mm
241.107	SS	K. Wire Ø 1.0 mm- L 250mm
241.109	SS	K. Wire Ø 1.0 mm- L 300mm
241.110	SS	K. Wire Ø 1.0 mm- L 310mm
241.119	SS	K. Wire Ø 1.2 mm- L 125mm
241.121	SS	K. Wire Ø 1.2 mm- L 150mm
241.122	SS	K. Wire Ø 1.2 mm- L 200mm
241.123	SS	K. Wire Ø 1.2 mm - L 250mm
241.124	SS	K. Wire Ø 1.2 mm- L 300mm
241.125	SS	K. Wire Ø 1.2 mm- L 310mm
241.141	SS	K. Wire Ø 1.4 mm- L 150mm
241.142	SS	K. Wire Ø 1.4 mm- L 200mm
241.143	SS	K. Wire Ø 1.4 mm- L 250mm



241.144	SS	K. Wire Ø 1.4 mm- L300mm
241.145	SS	K. Wire Ø 1.4 mm- L310mm
241.148	SS	K. Wire Ø 1.4 mm- L400mm
241.151	SS	K. Wire Ø 1.5 mm- L150mm
241.152	SS	K. Wire Ø 1.5 mm- L200mm
241.153	SS	K. Wire Ø 1.5 mm- L250mm
241.154	SS	K. Wire Ø 1.5 mm- L300mm
241.158	SS	K. Wire Ø 1.5 mm- L310mm
241.159	SS	K. Wire Ø 1.5 mm- L450mm
241.161	SS	K. Wire Ø 1.6 mm- L150mm
241.162	SS	K. Wire Ø 1.6 mm- L200mm
241.163	SS	K. Wire Ø 1.6 mm- L250mm
241.164	SS	K. Wire Ø 1.6 mm- L300mm
241.168	SS	K. Wire Ø 1.6 mm- L400mm
241.170	SS	K. Wire Ø 1.7 mm- L150mm
241.181	SS	K. Wire Ø 1.8 mm- L150mm
241.183	SS	K. Wire Ø 1.8 mm- L200mm
241.184	SS	K. Wire Ø 1.8 mm- L250mm
241.186	SS	K. Wire Ø 1.8 mm- L300mm
241.187	SS	K. Wire Ø 1.8 mm- L310mm
241.192	SS	K. Wire Ø 1.8 mm- L400mm
241.201	SS	K. Wire Ø 2.0 mm- L150mm
241.203	SS	K. Wire Ø 2.0 mm- L200mm
241.205	SS	K. Wire Ø 2.0 mm- L250mm
241.206	SS	K. Wire Ø 2.0 mm- L300mm
241.251	SS	K. Wire Ø 2.5 mm- L150mm
241.252	SS	K. Wire Ø 2.5 mm- L200mm
241.253	SS	K. Wire Ø 2.5 mm- L250mm
241.254	SS	K. Wire Ø 2.5 mm- L300mm
241.301	SS	K. Wire Ø 3.0 mm- L150mm
241.302	SS	K. Wire Ø 3.0 mm- L200mm
241.303	SS	K. Wire Ø 3.0 mm- L250mm
241.304	SS	K. Wire Ø 3.0 mm- L300mm



241.307	SS	K. Wire Ø 3.0 mm - L 400mm
241.353	SS	K. Wire Ø 3.5 mm- L 250mm
241.354	SS	K. Wire Ø 3.5 mm- L 300mm
241.426	SS	K. Wire Ø 2.5 mm- L 175mm
241.431	SS	K. Wire Ø 3.0 mm- L 175mm
792.115	TT	K. Wire Ø 1.5 mm- L 150mm
792.118	TT	K. Wire Ø 1.5 mm- L 200mm
792.120	TT	K. Wire Ø 1.5 mm- L 250mm
792.125	TT	K. Wire Ø 1.5 mm- L 300mm
792.215	TT	K. Wire Ø 2.0 mm- L 150mm
792.218	TT	K. Wire Ø 2.0 mm- L 230mm
792.220	TT	K. Wire Ø 2.0 mm- L 250mm
792.222	TT	K. Wire Ø 2.0 mm- L 300mm
792.250	TT	K. Wire Ø 2.5 mm - L 150mm
792.253	TT	K. Wire Ø 2.5 mm- L 230mm
792.255	TT	K. Wire Ø 2.5 mm- L 250mm
792.258	TT	K. Wire Ø 2.5 mm- L 280mm
792.260	TT	K. Wire Ø 2.5 mm- L 300mm
792.315	TT	K. Wire Ø 3.0 mm- L 150mm
792.318	TT	K. Wire Ø 3.0 mm- L 230mm
792.320	TT	K. Wire Ø 3.0 mm- L 250mm
792.324	TT	K. Wire Ø 3.0 mm- L 280mm
792.330	TT	K. Wire Ø 3.0 mm- L 300mm

Specification

- Kirschner's Wire (K. Wire) available in Stainless steel & Titanium.
- Available length 70-400 with 0.6,0.8,1.0,1.2,1.4,1.5,1.6,2.0,2.5 & 3.0mm dia.

Indication for use

- K Wires (Kirschner Wires) are used for temporary fixation during some operations. After definitive fixation they are then removed. The pins are usually removed four to five weeks post operation

